

10.1 INCH WIDE LCD1012

10.1" LED backlight LCD Monitor



Model No : LCD1012

LCD1012T / touch panel

- 10.1 inch wide LED backlight LCD Monitor
- HDMI/ DVI-D/ VGA/ Video x 2 inputs support
- 4-wire resistive touch panel model available
- Stepless adjustable stand with a low gravity center design
- VESA (FPMPI 75x75mm) hole support



Features

LCD1012 is a 10.1 inch LED backlit LCD monitor with HDMI, DVI-D, VGA and two video inputs using a customized SKS cable to enable easy cable management. The input resolution supports up to 1080p – digital, and 1920x1200 pixels – analog of LCD1012 adapts to a wide variety of applications including security, education, medical, digital signage, and FA.

■ Wide view angle support - 140/110 degree (H/V)

■ Customized SKS cable connection

Customized SKS cable contains 14 pins SKS terminal to 9 pins VGA, 2 x Video, Audio and DC input terminals which enables easy cable management.



■ 4-wire resistive touch panel model available

A convenient touch-screen model, LCD1012T is used as your input device. The touch screen model utilizes the USB port as the interface.

■ Multi-input signal support

LCD1012 supports both digital and analog input signals with variable input interfaces, HDMI, DVI-D, VGA and Video. LCD1012 also supports up to 1080P (digital) and 1600x1200 (analog) resolution input displaying the contents fit to the screen.

■ Stepless adjustable stand with a low gravity center design

LCD1012 has a stepless adjustable stand which enables bending and stretching to an ideal angle of your monitor installation. The rear of the stand also includes wall-mount hooks.



Specifications

Model	LCD1012
Panel Size	10.1"
Resolution	1024*600
touch panel	4-wire resistive, USB(option)
Brightness	250 cd/m2
Contrast Ratio	500:1
View Angle	140 (H) / 120 (V) degree
Input	HDMI, DVI-D, VGA, Video (RCA) x 2, Audio
Speaker	1W x 1 (mono)
VESA (FPMPI)	75 x 75 mm
DPMS	Yes
Power	DC12V 1.2A
Power Consumption	10W or less (operation) / 1W or less (power save mode)
Operating Temperature	0 to 50 degree
Storage Temperature	-20 to 60 degree
Dimension	254.4mm x 163mm x 34mm
Weight	1200g *excl. stand
Package Contents	Remote Controller, Customized SKS cable, HDMI cable, HDMI to DVI cable, Customized VGA cable (miniDIN 9pin to VGA), AC Adaptor, Manual, Touch pen (*1), Driver CD (*1)
Certification	FCC/ CE/ RoHS

*Specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here. Not responsible for typographical errors.
(*1) Only as for the touch panel model

Industrial LCD Monitors

Open Frame LCD Monitors

Option Accessories